
Electrospun Metal oxide nanofibers based H2S gas sensor

KID: 20231305

A tragedy that was a catastrophe and had no parallel in the world's industrial history. Tons of toxic gas leaked and spread throughout the city. Talking about estimated numbers, 10,000 people died, and 5,00,000 suffered. Yes, we are talking about the Bhopal gas tragedy of 1984. In another example, 12 people died, and more than 580 were injured; during a gas leakage at Vishakapatnam in 2020. How many more such gas leakage incidents do we suffer to understand that "prevention is better than cure." CARBON LAB at IIT Hyderabad jointly with Dr Mahesh Kumar (IIT Jodhpur) is working on detecting one of the most poisonous gases, H2S, through a flexible metal oxide gas sensor.



Although the permissible exposure limit (PEL) by Occupational Safety and Health Administration (OSHA) for H2S is 20-50 ppm,




Figure 1: Effects on Human body upon exposure to H2S gas

A tragedy that was a catastrophe and had no parallel in the world's industrial history. Tons of toxic gas leaked and spread throughout the city. Talking about estimated numbers, 10,000 people died, and 5.00.000 suffered. Yes, we are talking about the Bhopal gas tragedy of 1984. In another example, 12 people died, and more than 580 were injured; during a gas leakage at Vishakapatnam in 2020. How many more such gas leakage incidents do we suffer to understand that "prevention is better than cure." CARBON LAB at IIT Hyderabad jointly with Dr. Mahesh Kumar (IIT Jodhpur) is working on detecting one of the most poisonous gases, H2S, through a flexible metal oxide gas sensor.

it can cause severe damage to health and death if exposed to more than the permissible exposure limit. To detect H2S gas, utilize one-dimensional we synthesized nanofibers via electrospinning, as these provide high surface area and ease of surface functionalization. For the detection of H2S gas, we have utilized the electrical properties of metal oxide semiconductors that behave differently as the surrounding atmosphere changes. For better understanding, we selected SnO2 as the primary material due to its high chemical

sensitivity, faster gas response, and good thermal stability. A comparative study was done to understand the role of sensing material for H2S gas. Next, the SnO2 sensing was compared with CuO-decorated SnO2 nanofiber. The response for CuO-decorated SnO2 was at 200 °C hiaher operating temperature than the pristine SnO2 nanofiber. As the sensitivity of each material was high for H2S, our work concludes that SnO2 is a good material for detecting H2S gas. The sensing performance will be enhanced by functionalizing nanofibers with noble metals (Pt, Au, Ag, etc.) for low operating temperatures and using a flexible substrate for an easily portable device.

2

3

Reference:

1. Ruksana Shaik, Roopa Kishore Amit Kumar, Chandra Kampara. Shekhar Sharma, Mahesh Kumar, nanofibers "Metal oxide based chemiresistive H₂S das sensors",Coordination Chemistry Reviews,Vol. 471,2022, 214752. https://doi.org/10.1016/j.ccr.2022.214752

As the sensitivity of each material was high for H2S, our work concludes that SnO2 is a good material for detecting H2S gas.

[1] Prof Chandra Shekhar Sharma, [2] Shaik Ruksana, [3] Kampara Roopa Kishore

Creative & Advanced Research Based On Nanomaterials (CARBON) Laboratory, Department of Chemical Engineering,